

James Briggs Ltd

Salmon Fields, Royton, Oldham OL2 6HZ UK

Tel: 0161 627 0101 Fax: 0161 627 0971

www.jamesbriggs.co.uk

TECHNICAL DATA SHEET**LENS PAINT SMOKE****XUK436****1. Introduction**

A smoke grey decorative translucent finish designed primarily as a customising coating for the external surfaces of transparent acrylic plastics.

2. Where to use

Automotive and motorcycle headlamps, fog lamps and tail lights on show vehicles.

3. Where not to use

- On road going vehicles
- On painted, plastics or rubber surfaces.

4. Benefits

- Provides an expensive customised appearance.
- Improved aesthetics
- Easily removed with white spirit.

5. Physical properties [Lens paint base except where stated].

Appearance	Grey liquid with a characteristic paint solvent odour
pH	Not applicable
Specific Gravity	0.870 – 0.890
Viscosity	Semi viscous pourable liquid
Non Volatiles % m/m	10 - 20
Active Content % m/m, as supplied	10 - 20
Flammability, as supplied	Extremely Flammable, flash point below -20°C
Composition Data, as supplied	A solution of an acrylic resin in a solvent blend, containing an opacifying agent, and butane/propane/isobutane propellants.
Volatile Organic Content as supplied	Compliant with EU Directive 2004/42/CE
Service Temperatures	Up to 80°C
Application Temperatures	15 - 25°C

6. Application Details

Ensure the lens surfaces are clean, dry and free of all contamination including dirt, traffic film, oils, greases, waxes, etc. Ensure removal of all traces of silicones or silicone polishes. Mask off adjacent areas to avoid overspray.

Shake the can thoroughly for at least two minutes. Repeat shaking at regular intervals during use.

Apply sparingly from a distance of 20 – 25cm. Apply 2 to 3 light coats to achieve total and even coverage, allowing 10 – 15 minutes between applications.

Leave for 24 hours to achieve full hardness. On completion of use, invert can and depress actuator for a few seconds to prevent nozzle blockage.



James Briggs Ltd

Salmon Fields, Royton, Oldham OL2 6HZ UK

Tel: 0161 627 0101 Fax: 0161 627 0971

www.jamesbriggs.co.uk

TECHNICAL DATA SHEET

LENS PAINT SMOKE

XUK436

This product can be levelled and removed using HYCOTE DEGREASER [XUK441].

7. Availability

400ml. aerosols.

B0846440 August 2017.